
BookletChartTM


Harbors in Chatham Strait NOAA Chart 17337



A reduced-scale NOAA nautical chart for small boaters When possible, use the full-size NOAA chart for navigation.



- Complete, reduced-scale nautical chart
- Print at home for free
- Convenient size
- Up-to-date with Notices to Mariners
- Compiled by NOAA's Office of Coast Survey, the nation's chartmaker



Published by the National Oceanic and Atmospheric Administration National Ocean Service Office of Coast Survey

<u>www.NauticalCharts.NOAA.gov</u> 888-990-NOAA

What are Nautical Charts?

Nautical charts are a fundamental tool of marine navigation. They show water depths, obstructions, buoys, other aids to navigation, and much more. The information is shown in a way that promotes safe and efficient navigation. Chart carriage is mandatory on the commercial ships that carry America's commerce. They are also used on every Navy and Coast Guard ship, fishing and passenger vessels, and are widely carried by recreational boaters.

What is a BookletChart[™]?

This BookletChart is made to help recreational boaters locate themselves on the water. It has been reduced in scale for convenience, but otherwise contains all the information of the full-scale nautical chart. The bar scales have also been reduced, and are accurate when used to measure distances in this BookletChart. See the Note at the bottom of page 5 for the reduction in scale applied to this chart.

Whenever possible, use the official, full scale NOAA nautical chart for navigation. Nautical chart sales agents are listed on the Internet at http://www.NauticalCharts.NOAA.gov.

This BookletChart does NOT fulfill chart carriage requirements for regulated commercial vessels under Titles 33 and 44 of the Code of Federal Regulations.

Notice to Mariners Correction Status

This BookletChart has been updated for chart corrections published in the U.S. Coast Guard Local Notice to Mariners, the National Geospatial Intelligence Agency Weekly Notice to Mariners, and, where applicable, the Canadian Coast Guard Notice to Mariners. Additional chart corrections have been made by NOAA in advance of their publication in a Notice to Mariners. The last Notices to Mariners applied to this chart are listed in the Note at the bottom of page 7. Coast Pilot excerpts are not being corrected.

For latest Coast Pilot excerpt visit the Office of Coast Survey website at http://www.nauticalcharts.noaa.gov/nsd/searchbychart.php?chart=173 <a href="http://www.nauticalcharts.noaa.gov/nsd/searchbycharts.noaa



(Selected Excerpts from Coast Pilot)
Warm Spring Bay is on the W side of
Chatham Strait, about 56 miles N of Cape
Ommaney and 7 miles NW of Point
Gardner. The bay has good anchorage for
small craft, but the anchorage for large
vessels is indifferent.

Warm Spring Bay Light (57°04'48"N., 134°46'32"W.), 27 feet above the water, is shown from a skeleton tower with a red and white diamond-shaped daymark on the S point of the entrance. A microwave

tower, about 1 mile WNW of the light on a knob along the N shore, is prominent at the entrance to the bay. At the head of the bay is a

waterfall, visible from Chatham Strait, and near the waterfall are several warm mineral springs.

Warm Spring Bay is of easy access, and with the chart as a guide no trouble should be experienced in entering. Midchannel courses are recommended.

Two small bights in the S shore afford anchorage for small craft. The W one is preferable, because of shoaler water, from 12 to 15 fathoms. The only anchorage in the bay for large vessels is off the W bight in 25 fathoms, but the bottom is rocky and the current from the cascade sets out, making a vessel lie broadside to SE winds that draw into the bay. A shoal with a depth of 6½ fathoms is about 200 yards offshore and about 230 yards E of Warm Spring Bay Light. There may be less water, so it should be avoided when entering the bay. Care should be taken to avoid the reef that makes out 60 yards from the N shore at a point about 200 yards E of Baranof.

Takatz Bay has its entrance on the W side of Chatham Strait about 10.5 miles NW of Point Gardner and 16 miles S of Point Thatcher. It terminates in a flat about 0.4 mile in extent, formed by a mountain stream emptying as a waterfall.

Point Turbot, the N point at the entrance to Takatz Bay, is marked by **White Rock**, a large white rock about 50 yards off. A high waterfall about 2 miles N of Point Turbot is visible from N a considerable distance. **Kasnyku Bay**, on the W side of Chatham Strait about 14 miles NW of Point Gardner, has deep water and no secure anchorage.

The entrance to the bay is between **North Point** and **Round Island**, and its surrounding group of small islets, off the S point of the entrance. **Cosmos Cove** is on the W side of Chatham Strait about 5.5 miles N of Takatz Bay and 2 miles S of Kelp Bay. The cove affords anchorage with good shelter in 10 to 15 fathoms, soft bottom, for small vessels. The head of the cove is shoal for a distance of about 0.8 mile.

Kelp Bay (57°17'N., 134°51'W.), a large indentation in the NE coasts of Baranof Island, is 10.5 miles S of the E entrance of Peril Strait and 17.5 miles NNW of Point Gardner. Its entrance is between **North Point** the S extremity of Catherine Island, and **South Point** on Baranof Island. The bay has no known commercial activity.

The main bay extends about 3.5 miles NW where it divides into three arms. **Middle Arm** extends in a W direction. **South Arm** extends in a general SW direction. **The Basin**, in the S part of the bay, is bordered on the E by two groups of islands that include **Pond Island**, **Crow Island**, and other adjacent islands. **Portage Arm**, which extends in a NW direction, is reported to connect with Hanus Bay, in Peril Strait, by an overgrown portage.

Anchorages.—Anchorages in the bay are few, the best being in the SE corner of The Basin. Another is in Middle Arm about 0.8 mile from its head in 22 to 25 fathoms, soft bottom. A small vessel can find temporary anchorage in Portage Arm about 2.7 miles above the entrance in midchannel, in 10 fathoms, but this anchorage has scant swinging room and is exposed to SE winds that draw through the arm.

Dangers.—The survey of the bay is old and incomplete, and dangers may exist in addition to those shown on the chart. The known dangers include shoal water that extends 0.4 mile S of North Point; ledges that extend off South Point; extensive shoals and dangerous rocks in the cove on the SE side of Pond Island; Yellow Rock and the shoals SE, S, and WNW of it.

U.S. Coast Guard Rescue Coordination Center 24 hour Regional Contact for Emergencies

RCC Juneau Commander

17th CG District (907) 463-2000 Juneau, Alaska

2

Corrected through NM Mar. 03/12 Corrected through LNM Feb. 21/12

HEIGHTS

Heights in feet above Mean High Water.

Mercator Projection Scale 1:20,000 at Lat. 57°05' North American Datum of 1983 (World Geodetic System 1984)

CAUTION

Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.

NOTE A

Navigation regulations are published in Chapter 2, U.S. Coast Pilot 8. Additions or revisions to Chapter 2 are published in the Votice to Mariners. Information concerning he regulations may be obtained at the Office of the Commander, 17th Coast Guard District allowed by the Commander, 17th Coast Guard District Chapter 4. Business Allowed Services (1998). Juneau, Alaska, or at the Office of the District

Refer to charted regulation section numbers

AUTHORITIES

Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the U.S. Coast Guard.

HORIZONTAL DATUM

The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84). Geographic positions referred to the North American Datum of 1927 must be corrected an average of 1.211" southward and 6.320" westward to agree with this chart.

AIDS TO NAVIGATION

Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.

NOAA WEATHER RADIO BROADCASTS

The NOAA Weather Radio stations listed below provide continuous weather broadcasts. The reception range is typically 20 to 40 nautical miles from the antenna site, but can be as much as 100 nautical miles for stations at high elevations.

 Mt. McArthur, AK
 KZZ-95
 162.525 MHz

 Mt. Robert Barron, AK
 KZZ-87
 162.425 MHz

 Cape Fanshaw, AK
 KZZ-88
 162.425 MHz

 Althorp Peak, AK
 KZZ-86
 162.425 MHz

LOCAL MAGNETIC DISTURBANCE Differences of as much as 6° from the norm variation have been observed along the southeaster coast of Catherine Island.

RADAR REFLECTORS

Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

COLREGS: International Regulations for Preventing Collisions at Sea, 1972.

Exercise extreme caution when transiting the areas adjacent to Ponc sland and southeast of Portage Point. Previously uncharted shoals

The contour lines are hill shapes, sketched to afford the navigator a generalized indication of the character of the land forms. They should not be relied upon as lines of equl elevation.

SOURCE DIAGRAM

The outlined areas represent the limits of the most recent hydrographic survey information that has been evaluated for charting. Surveys have been banded in this diagram by date and type of survey. Channels maintained by the U.S. Army Corps of Engineers are periodically resurveyed and are not shown on this diagram. Refer to Chapter 1, <u>United States Coast Pilot.</u>

POLLUTION REPORTS

Report all spills of oil and hazardous substances to the National Response Center via 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

International Regulations for Preventing Collisions at Sea, 1972. The entire area of this chart falls seaward of the COLREGS Demarcation Line

Table of Selected Chart Notes

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast

ABBREVIATIONS (For complete list of Symbols and Abbreviations, see Chart No. 1.)

AERO aeronautical	G green	Mo morse code	R TR radio tower
Al alternating	IQ interrupted quick	N nun	Rot rotating
B black	Iso isophase	OBSC obscured	s seconds
Bn beacon	LT HO lighthouse	Oc occulting	SEC sector
C can	M nautical mile	Or orange	St M statute miles
DIA diaphone	m minutes	Q quick	VQ very quick
F fixed	MICRO TR microwave tower	R red	W white
FI flashing	Mkr marker	Ra Ref radar reflector	WHIS whistle
		R Bn radiobeacon	Y yellow

Bids boulders gy gray Oys oysters Rk rock so soft Sh shells bk broken G gravel Cy clay Grs grass S sand

Miscellaneous: AUTH authorized ED existence doubtful Obstn obstruction PA position approximate PD position doubtful Subm submerged

Rep reported 21. Wreck, rock, obstruction, or shoal swept clear to the depth indicated.

 $(\underline{2})$ Rocks that cover and uncover, with heights in feet above datum of soundings


TIDAL INFORMATION

PLACE		Height referred to datum of soundings (MLLW)		
NAME	(LAT/LONG)	Mean Higher High Water	Mean High Water	Mean Low Water
Port McArthur Baranof, Warm Spring Bay Kasnyku Bay	(56°04'N/134°07'W) (57°05'N/134°50'W) (57°13'N/134°52'W)	13.4	feet 9.7 12.5 12.9	feet 1.5 1.5

Dashes (- - -) located in datum columns indicate unavailable datum values for a tide station. Real-time water levels, tide predictions, and tidal current predictions are available on the Internet from http://tidesandcurrents.noaa.gov.


SOUNDINGS IN FATHOMS


This nautical chart has been designed to promote safe navigation. The National Ocean Service encourages users to submit corrections, additions, or comments for improving this chart to the Chief, Marine Chart Division (N/CS2), National Ocean Service, NOAA, Silver Spring, Maryland 20910-3282.




4

















with true north.






















10







12



Joins page 9



THE NATION'S CHARTMAKER SINCE 1807

UNITED STATES

ALASKA - SOUTHEAST COAST

HARBORS IN CHATHAM STRAIT

SOUNDINGS IN FATHOMS

AT MEAN LOWER LOW WATER

Additional information can be obtained at nauticalcharts.noaa.gov.

ABBREVIATIONS (For complete list of Symbols and Abbrevi Aids to Navigation (lights are white unless otherwise indicated): (For complete list of Symbols and Abbreviations, see Chart No. 1.)

G green AERO aeronautical R TR radio tower Mo morse code Al alternating IQ interrupted quick Iso isophase N nun Rot rotating OBSC obscured Oc occulting Or orange s seconds SEC sector St M statute miles LT HO lighthouse M nautical mile m minutes DIA diaphone Q quick R red VQ very quick MICRO TR microwave tower W white FI flashing Ra Ref radar reflector WHIS whistle R Bn radiobeacon Y yellow Bottom characteristics: Bids boulders gy gray Oys oysters

so soft Sh shells bk broken G gravel h hard M mud Cy clay Grs grass S sand sy sticky

Miscellaneous: AUTH authorized

Obstn obstruction PD position doubtful

ED existence doubtful PA position approximate Repreported 21. Wreck, rock, obstruction, or shoal swept clear to the depth indicated.

(2) Rocks that cover and uncover, with heights in feet above datum of soundings

COLREGS: International Regulations for Preventing Collisions at Sea, 1972.

TIDAL INFORMATION

PLACE		Height referred to datum of soundings (MLLW)		
NAME	(LAT/LONG)	Mean Higher High Water	Mean High Water	Mean Low Water
Port McArthur Baranof, Warm Spring Bay Kasnyku Bay	(56°04'N/134°07'W) (57°05'N/134°50'W) (57°13'N/134°52'W)	13.4	feet 9.7 12.5 12.9	feet 1.5 1.5
Dashes () located in datum colur	nns indicate unavailable datur	m values for a tid	e station. Real-ti	me water levels.

tide predictions, and tidal current predictions are available on the Internet from http://tidesandcurrents.ncaa.gov.

HEIGHTS

Heights in feet above Mean High Water.

AUTHORITIES

Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the U.S. Coast Guard.

HORIZONTAL DATUM

The horizontal reference datum of this chart is North American Datum of 1983 (NAD 83), which for charting purposes is considered equivalent to the World Geodetic System 1984 (WGS 84).
Geographic positions referred to the North
American Datum of 1927 must be corrected an average of 1.211" southward and 6.320" westward to agree with this chart.

AIDS TO NAVIGATION

Consult U.S. Coast Guard Light List for supplemental information concerning aids to

SUPPLEMENTAL INFORMATION

Consult U.S. Coast Pilot 8 for important supplemental information

CAUTION

Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.

COLREGS, 80.1705 (see note A)

International Regulations for Preventing Collisions at Sea, 1972. The entire area of this chart falls seaward of the COLREGS Demarcation Line.

POLLUTION REPORTS

Subm submerged

Report all spills of oil and hazardous substances to the National Response Center via 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

WARNING

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details

The contour lines are hill shapes, sketched to afford the navigator a generalized indication of the character of the land forms. They should not be relied upon as lines of equl elevation.

Navigation regulations are published in Chapter 2, U.S. Coast Pilot 8. Additions or revisions to Chapter 2 are published in the Notice to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 17th Coast Guard District in Juneau, Alaska, or at the Office of the District. Engineer, Corps of Engineers in Anchorage

Refer to charted regulation section numbers.

NOAA WEATHER RADIO BROADCASTS

The NOAA Weather Radio stations listed below provide continuous weather broadcasts. The reception range is typically 20 to 40 nautical miles from the antenna site, but can be as much as 100 nautical miles for stations at high elevations.

KZZ-95 162.525 MHz KZZ-87 162.450 MHz KZZ-88 162.425 MHz Mt. McArthur, AK Mt. Robert Barron, AK Cape Fanshaw, AK Althorp Peak, AK KZZ-86 162.425 MHz

veekly by NOAA for Notices to Mariners g Print-on-Demand technology. New hal NOAA charts. Ask your chart agent ata.ncd.noaa.gov/idrs/inquiry.aspx, or

Published at Washington, D.C U.S. DEPARTMENT OF COMMERCE NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION NATIONAL OCEAN SERVICE COAST SURVEY



STATES

JTHEAST COAST

HATHAM STRAIT

IN FATHOMS

WER LOW WATER

obtained at nauticalcharts.noaa.gov

nd Abbreviations, see Chart No. 1.)

dicated):

R TR radio tower Mo morse code Rot rotating s seconds SEC sector St M statute miles N nun OBSC obscured Oc occulting Or orange

Q quick R red VQ very quick W white WHIS whistle Y yellow Ra Ref radar reflector R Bn radiobeacon

Oys oysters Rk rock so soft Sh shells nard mud S sand sy sticky

PD position doubtful Subm submerged

clear to the depth indicated. hts in feet above datum of soundings enting Collisions at Sea, 1972.

NFORMATION

		Height referred to datum of soundings (MLLW)				
13		Mean Higher High Water	Mean High Water	Mean Low Water		
page	.M) (M,	feet 10.6 13.4 13.8	feet 9.7 12.5 12.9	feet 1.5 1.5		
Su		m values for a tide station. Real-time water levels, Internet from http://tidesandcurrents.ncaa.gov.				
Joi		Papart all	apilla of oil o	POLLUTION		

POLLUTION REPORTS

Report all spills of oil and hazardous substances to the National Response Center via 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

WARNING

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details

The contour lines are hill shapes, sketched to afford the navigator a generalized indication of the character of the land forms. They should not be relied upon as lines of equl elevation.

NOTE A

NOTE A

Navigation regulations are published in Chapter 2, U.S. Coast Pilot 8. Additions or revisions to Chapter 2 are published in the Notice to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 17th Coast Guard District in Juneau, Alaska, or at the Office of the District Engineer, Corps of Engineers in Anchorage, Alaska


Refer to charted regulation section numbers.

NOAA WEATHER RADIO BROADCASTS


The NOAA Weather Radio stations listed below provide continuous weather broadcasts. The reception range is typically 20 to 40 nautical miles from the antenna site, but can be as much as 100 nautical miles for stations at high elevations.


KZZ-95 162.525 MHz KZZ-87 162.450 MHz KZZ-88 162.425 MHz KZZ-86 162.425 MHz Mt. McArthur, AK Mt. Robert Barron, AK Cape Fanshaw, AK Althorp Peak, AK

> Published at Washington, D.C U.S. DEPARTMENT OF COMMERCE NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION NATIONAL OCEAN SERVICE COAST SURVEY



SOUNDIN







VHF Marine Radio channels for use on the waterways:

Channel 6 – Inter-ship safety communications.

Channel 9 – Communications between boats and ship-to-coast.

Channel 13 – Navigation purposes at bridges, locks, and harbors.

Channel 16 – Emergency, distress and safety calls to Coast Guard and others, and to initiate calls to other

vessels. Contact the other vessel, agree to another channel, and then switch.

Channel 22A – Calls between the Coast Guard and the public. Severe weather warnings, hazards to navigation and safety warnings are broadcast here. Channels 68, 69, 71, 72 and 78A – Recreational boat channels.

Getting and Giving Help — Signal other boaters using visual distress signals (flares, orange flag, lights, arm signals); whistles; horns; and on your VHF radio. You are required by law to help boaters in trouble. Respond to distress signals, but do not endanger yourself.

Distress Call Procedures

- Make sure radio is on.
- Select Channel 16.
- Press/Hold the transmit button.
- Clearly say: "MAYDAY, MAYDAY, MAYDAY."
- Also give: Vessel Name and/or Description; Position and/or Location; Nature of

Emergency; Number of People on Board.

- · Release transmit button.
- Wait for 10 seconds If no response Repeat MAYDAY call.

HAVE ALL PERSONS PUT ON LIFE JACKETS!



NOAA Weather Radio All Hazards (NWR) is a nationwide network of radio stations broadcasting continuous weather information directly from the nearest National Weather Service office. NWR broadcasts official Weather Service warnings, watches, forecasts and other hazard information 24 hours a day, 7 days a week.

http://www.nws.noaa.gov/nwr/

Quick References

Nautical chart related products and information — http://www.nauticalcharts.noaa.gov

Online chart viewer — http://www.nauticalcharts.noaa.gov/mcd/NOAAChartViewer.html

Report a chart discrepancy — http://ocsdata.ncd.noaa.gov/idrs/discrepancy.aspx

Chart and chart related inquiries and comments — http://ocsdata.ncd.noaa.gov/idrs/inquiry.aspx?frompage=ContactUs

Chart updates (LNM and NM corrections) — http://www.nauticalcharts.noaa.gov/mcd/updates/LNM_NM.html

Coast Pilot online — http://www.nauticalcharts.noaa.gov/nsd/cpdownload.htm

Tides and Currents — http://tidesandcurrents.noaa.gov

Marine Forecasts — http://www.nws.noaa.gov/om/marine/home.htm

National Data Buoy Center — http://www.ndbc.noaa.gov/

NowCoast web portal for coastal conditions — http://www.nowcoast.noaa.gov/

National Weather Service — http://www.weather.gov/

National Hurrican Center — http://www.nhc.noaa.gov/

Pacific Tsunami Warning Center — http://ptwc.weather.gov/

Contact Us — http://www.nauticalcharts.noaa.gov/staff/contact.htm



For the latest news from Coast Survey, follow @nauticalcharts



This Booklet chart has been designed for duplex printing (printed on front and back of one sheet). If a duplex option is not available on your printer, you may print each sheet and arrange them back-to-back to allow for the proper layout when viewing.

